SHARP



Check out this compact LCD projector - the Notevision C40. From color-coded user interface points and easily identifiable icon-based adjustment buttons, to full automatic synchronization of images and input sources. This projector is bound to make your life a little easier.

The Notevision C40 will accept input signals ranging from VGA and SVGA to it's native XGA resolution and up to 1600 x 1200 (UXGA). It projects each input mode in exacting detail without the need for any manual adjustments.

It's compatible, versatile, and very easy to use. Just plug it in to your data or video source and let the presentation begin. Your audience will love it.

The Notevision C40 may be compact, but with 2000 ANSI lumens this small package will create major impact.

Truly presentation technology at its best!

ADVANCED FEATURES

- 2000 ANSI Lumens Brightness with 90% Uniformity (CCR)
- S.A.P.S. for Remote Projector Control and Self Diagnostics
- Two Separate Data Inputs for PC or Mac plus Monitor Out
- Two Separate Video Inputs (Composite and S-Video)
- "autoSYNC" for Automatic Image Perfection
- Intelligent ImageACE Resizing
- 1.3:1 x Manual Zoom/Focus Lens
- International Power Supply (100-240V AC)
- Wireless "Power Remote" with Mouse Control and Laser Pointer
- Built-in 3 watt Audio System
- Digital Keystone Correction with Edge Smoothing
- 3D Digital Uniformity
- Designed to Fit in an Airplane Overhead Complete w/ Notebook PC
- "PresenterPAK", The Sharp Exclusive Feature-set Making it Simple to "Connect, Perfect, Project"
- DTV Compatible 480i/480p/720p/1080i

PROJECTION DISTANCES

Screen Diagonal	Screen Width	Screen Height	Minimum Distance	Maximum Distance
40"	32"	24"	4'8"	6'1"
60"	48"	36"	7'1"	9'3"
84"	67"	50"	9'11"	13'1"
100"	80"	60"	11'11	15'6"
150"	120"	90"	17'8"	23'1"
200"	160"	120"	23'6"	30'7"
300"	240"	180"	35'4"	46'

Approx. Min / Max Projection Distance from Screen to Front of Lens

*Design and specifications are subject to change without notice. All trademarks are property of their respective holders.

SPECIFICATIONS

XGA (1024 x 768) Resolution TV Lines 750 TV Lines

Panel Type 3 - 0.9" Polysilicon TFT LCD H & V Frequency fH 15-126 kHz / fV 43 - 200 Hz

Dot Clock 230 MHz

PC Compatibility UXGA (1600 x 1200) w/ ImageACE Resizing Mac Compatibility 21" up to 1280x1024 w/ ImageACE Resizing

WS Compatibility 1280 x 1024 (various modes w/ ImageACE Resizing)

NTSC/DTV/PAL/SECAM - Interlaced or Progressive Scan DTV/HD Compatible 480i/480p/720p/1080i Video System

Resizing Advanced ImageACE Resizing - up to UXGA

Brightness 2000 ANSI Lumens w/ 90% CCR

Contrast Ratio 400:1

Lens Type 1.3:1 Manual Zoom and Focus

PC Control RS-232C

Remote Control IR w/ Mouse Control, Laser Pointer

IR Carrier Frequency 38 kHz

Audio System 3 Watt Monaural

200 NSH, User Replaceable Lamp

Lamp Part No. BQC-XGC40XU/1

Fan Noise 39 dB

Power Source 100-240V AC, 50/60Hz

Power Consumption 300 Watt

Heat Dissipation 1.130 BTU/hour

Dimensions 9.0" x 4.8" x 12.2" (main body)

Weight 10.6 lbs.

Limited Warranty 3 Yrs. Parts/Labor & 3 Yrs. Sharp Express Repair,

Lamp 90 Days

Presentation Tools "PresenterPAK"

INPUTS/OUTPUTS

- 2 RGB/Computer Inputs [15 pin HD Female]
- 1 Computer/RGB Output [15 pin HD Female]
- 2 Separate Video Inputs [Composite (RCA) and S-Video (4 pin DIN)]
- 2 Stereo Audio Inputs (RCA pair L/R; 3.5mm Stereo Minijack)
- 1 Audio Out (3.5mm Stereo Minijack)
- 1 RS-232C Serial Port (9 pin D-sub Male)

INCLUDED ACCESSORIES

Backlit Wireless Remote with Laser Pointer and Mouse Control, Two AA batteries, 9' RGB Signal Cable, 12' Grounded AC Cord, 270° Wireless Mouse IR Receiver, USB Mouse Adapters, 9' Audio cable, DIN DSub RS-232C adapter, Air Filter, Lens Cap, Owners Manual, Sharp Advanced Presentation Pro Software (S.A.P.S.)

OPTIONAL ACCESSORIES

AN-C100PCBAG Soft Sided Carry-on Bag (projector & PC) AN-C100BAG Soft Sided Carry-on Bag (projector only) AN-C100CC Hard Shell Carrying Case (projector only) Hard Sided Bag w/wheels (projector & PC) AN-C100WB AN-C100SC "ATA" Style Shipping Case for Projector

AN-XGCM53 Ceiling Mounting Bracket AN-EP101B

Extension Tube for Ceiling Mount AN-JT200 Angle Mount Joint for Ceiling Mount

SHARP ELECTRONICS CORPORATION

LCD Products Group, Sharp Plaza, Mahwah, NJ 07430-2135 E-mail: ProLCD@SharpSEC.com

1-888-GO-SHARP

www.SharpLCD.com/Notevision





Printed in USA I C-02-219 Rev 9.0 Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com