CDM™*SNT*

Wall-mount loudspeaker

Product Summary

- The CDM SNT combines practicality and elegance with an array of technological features.
- Practically designed with its shallow profile and contoured cabinet edges the speaker can easily be mounted to a wall with the compact bracket which is supplied and fitted to the rear of the speaker.
- Available in a choice of real wood veneers to compliment the rest of the CDM NT range.

Technical highlights



Nautilus™ Tweeter : B&W's Nautilus™ Tweeter technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



Description 50W - 120W into 8 ohm on unclipped 2-way closed-box system Power handling Drive units 1 x 25mm alloy dome high-frequency programme 1 x 165mm woven Kevlar® cone Dimensions Height: 394mm Width: 392mm Finishes Cabinet: Real wood veneers, Black Ash,

Frequency response 75Hz – 20kHz ± 3dB on reference

Sensitivity 90dB spl (2.83V, 1m) Nominal impedance 8 (min 4.8)

Cherrywood, Red Stained Cherrywood

Grilles: Black cloth



Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com