

MODEL H2881 4" PNEUMATIC DRUM SANDER

INSTRUCTION SHEET

AWARNING



EYE/EAR INJURY HAZARD! Wear safety glasses and hearing protection during use of this tool!



OVER INFLATION HAZARD! Never exceed 8 PSI!



RESPIRATORY HAZARD! Sanding produces fine dust. Wear the appropriate protection during use!

Introduction

This rolling-pin style pneumatic drum sander is perfect for hand contouring and smoothing projects that are too large to use with a stationary sander. Simply chuck the $^3/_8$ " spindle into a portable electric drill, cordless drill or air powered drill for two-handed control. Choose this 4" x $^{11}/_8$ " diameter size for getting into tight areas. Features ball bearing handle and air valve for easy bicycle pump inflation.

Inventory

Α.	Drum Sander	1
B.	Spare Valve Cap	1

Operation

Slide the sanding sleeve over the drum. Remove the plastic cap on the handle with a small screw driver to expose the air valve. Inflate to the desired pressure. DO NOT exceed 8 PSI!



Figure 1. Model H2881.




Figure 2. Pneumatic drum sander in action.

4" Aluminum Oxide Sanding Sleeves

H3875 11/8" x 4" x 60 Grit **H3876** 11/8" x 4" x 100 Grit

H3877 1½" x 4" x 150 Grit **H3878** 1½" x 4" x 180 Grit

H3879 11/8" x 4" x 220 Grit

H3880 11/8" x 4" x 320 Grit

If you need help with your new pneumatic tool, call our Tech Support at: (570) 546-9663.

COPYRIGHT © MARCH, 2006 BY GRIZZLY INDUSTRIAL, INC.

WARNING: NO PORTION OF THIS MANUAL MAY BE REPRODUCED IN ANY SHAPE
OR FORM WITHOUT THE WRITTEN APPROVAL OF GRIZZLY INDUSTRIAL, INC.

#PC8119 PRINTED IN TAIWAN

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com